## PRODUCT SPECIFICATIONS



## 8077FDQC

## FT-Arc™ Flash 2D Climbing Non-Belted Full Body Harness, Overmolded Quick Connect Adjustments

## Features:

- Comfort Legs™ lateral leg strap construction greatly improves mobility and comfort
- Features premium overmolded alloy steel dorsal and sternal D-rings, quick-connect leg and chest buckles, and torso adjusters
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, belt, and legs.
- Shoulder yoke and sub-pelvic leg pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection
- Overmolded quick-connect buckle feature visual indicator showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Includes Arc Flash rated Suspension Trauma Relief Straps
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2021

Material Specifications						
Webbing	Nomex®/Kevlar®; 5,000 lb min. static strength					
D-rings	Overmolded Alloy Steel; 5,000 lb min. static strength					
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength					

Performance Spe	cifications		
Static Strength	3,600 lb min.		
ANSI User	130 to 310 l		
Capacity	max.		
OSHA User	130 to 425 lb		
Capacity	max.		

Com	pliant With:
OSHA	1926.502 and 1910.66
ASTM	F887-20
ANSI	Z359.11-2021

Sizes & Part Numbers						
8077FDQCXS	8077FDQCS	8077FDQCM	8077FDQCL	8077FDQCXL	8077FDQC2X	8077FDQC3X
- XS	- S	- M	- L	- XL	- 2X	- 3X