

7086BFD

FlowTech LTE® 2D Climbing Non-belted Full Body Harness, Tongue Buckle Leg Adjustment

Features :

- Lightweight Flowscape® shoulder yoke and sub-pelvic leg pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal and sternal D-rings
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Meets OSHA 1926.502 and 1910.66 Regulations



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-rings	Aluminum alloy; 5,000 lb min. static strength
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
CSA	Z259.10-2018
OSHA	1926.502 and 1910.66

Sizes & Part Numbers				
7086BFDS - Small	7086BFDM - Medium	7086BFDL - Large	7086BFDXL - XL	+