

## 7276100

### Contractor SRL with 100' Galvanized Cable and Anchorage Carabiner

#### Features :

- 3/16" galvanized steel cable lifeline with load-indicating swivel snap hook
- Features glass-filled nylon housing for durable impact resistance.
- Lifeline includes recoil spring bumper to reduce retraction lock-up
- Rugged internal steel drum and inertial braking system deliver reliable performance
- SRL includes double-locking twist-lock anchorage carabiner
- Complies with ANSI Z359.14-2014

Material Specifications	
<b>Cable</b>	3/16" galvanized steel; 3,400 lb min. static strength
<b>Lifeline Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	3,000 lb min.
<b>ANSI SRL Class</b>	Class B
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	54"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.14-2014

Sizes & Part Numbers					
727620 -20' (ANSI Compliant)	727630C - 30' (ANSI Compliant)	C727630 - 30' (CSA Compliant)	727650C - 50' (ANSI Compliant)	C727650 - 50' (CSA Compliant)	7276100 - 100' (ANSI Compliant)