

82909SC3

9' Arc Flash DuraTech® MAX Personal SRL with Steel Rebar Hook

Features :

- Internal inertial brakes plus the external energy absorber deliver max weight capacity and max below D-ring anchorage distance
- Kevlar® web lifeline protects against Arc Flash hazards.
- Overmolded glass-filled nylon housing contributes unmatched impact resistance
- Energy absorber features Nomex® ViewPack® cover with inspection window and WrapPack label protection
- Integrated aluminum alloy swivel-eye helps to prevent lifeline twisting for smooth operation
- Features alloy steel rebar hook anchorage connector
- Rebar hook features transverse load rated gate
- Includes aluminum alloy dorsal connecting carabiner
- May be anchored up to 5' below the dorsal D-ring for users weighing up to 425 lb max. with OSHA-only compliance
- Complies with ANSI Z359.14-2014 and ASTM F887-13

Material Specifications	
Webbing	Kevlar®; 4,500 lb min.
Energy Absorber	Polyester tear-away
Anchorage Connector	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,000 lb min.
ANSI SRL Class	Class B
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	54"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ASTM	F887-13
ANSI	Z359.14-2014