

## 82909TB5

### 9' Arc Flash DuraTech® MAX Personal SRL with Aluminum Rebar Hooks

#### Features :

- Internal inertial brakes plus the external energy absorber deliver max weight capacity and max below D-ring anchorage distance
- Kevlar® web lifeline protects against Arc Flash hazards.
- Overmolded glass-filled nylon housings contribute unmatched impact resistance
- Energy absorbers feature Nomex® ViewPack® covers with inspection windows and WrapPack label protection
- Integrated aluminum alloy swivel-eyes help to prevent lifeline twisting for smooth operation
- Features aluminum alloy rebar hook anchorage connectors
- Rebar hooks feature transverse load rated gates
- Includes alloy steel dorsal connecting carabiner with twin-leg alignment clip
- May be anchored up to 5' below the dorsal D-ring for users weighing up to 425 lb max. with OSHA-only compliance
- Complies with ANSI Z359.14-2014 and ASTM F887-13

#### Material Specifications

<b>Webbing</b>	Kevlar®; 4,500 lb min.
<b>Energy Absorber</b>	Polyester tear-away
<b>Anchorage Connector</b>	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Dorsal Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

#### Performance Specifications

<b>Static Strength</b>	3,000 lb min.
<b>ANSI SRL Class</b>	Class B
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	54"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.

#### Compliant With:

<b>OSHA</b>	1926.502 and 1910.66
<b>ASTM</b>	F887-13
<b>ANSI</b>	Z359.14-2014