



Latitude Edge Tie-Back 7' Cable SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Durable stainless steel housing with nylon sides.
- Frameless design creates thinner housing size.
- Exclusive dorsal attachment bracket with SRL separator feature.
- Compact shock pack design with harness restraint strap.
- 360/180° attachment point offers full range of motion.
- Side payout for smooth retraction.
- Protective label cover for product longevity and traceability.
- RFID equipped.
- Designed for sharp leading edges with foot-level connection.
- 20" or 40" web extension with tie-back snap hook for wrapping around your anchor point.
- Single leg and dual leg options available.
- All components are Z359.12 compliant.



Class
2
Anchor above or
below dorsal D-ring

Product shown:
023-5360

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 36 in. (91 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 6 in. (2 m)* *Based on full utilization of tie-back leg. For other connections, see manual.

For full clearance requirements, see user instructions

ANSI CLASS 2

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	*See product manual
Max. free fall distance	*See product manual
Min. required fall clearance	*See product manual
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Cable	3/16" galvanized steel
Tie-Back Web Extension	Specialized composite webbing
Bracket	Steel and aluminum
Housing	Stainless steel and nylon
Snap Hook	Zinc-plated steel
Shock pack	Polyester



Latitude Edge Tie-Back 7' Cable SRL-P



Standards: ANSI Z359.14-2021
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	Steel Snap Hook ①	Li Steel Swivel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	Li Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	Steel Captive Eye Carabiner ⑧	ALU Captive Eye Carabiner ⑨	ALU Swivel Carabiner ⑩	Tip Lock Steel Carabiner ⑪	Steel Carabiner ⑫	ALU Captive Eye Carabiner ⑬	ALU Carabiner ⑭	ALU Snap Hook ⑮	ES-EG33 ⑯	Cable Mount Bracket ⑰	Soft Loop ⑱	Integrated BWP ⑲	10-14 BWP ⑳	9012 BWP ㉑	9013 BWP ㉒
023-5360	2 S	7	Steel Cable	Ø3/16	Nylon/SS	5.0					X														X			
023-5361	2 D	7	Steel Cable	Ø3/16	Nylon/SS	8.8					X														X			
023-5362	2 S	7	Steel Cable	Ø3/16	Nylon/SS	5.1					X														X			
023-5363	2 D	7	Steel Cable	Ø3/16	Nylon/SS	8.9					X														X			

