



023-5325

Lodestar LE 30' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- External energy absorber for leading edge use.
- Swivel attachment point offers wide range of motion.
- High strength housing for durability.
- Built-in handle for convenience.
- Optimized walking speeds to reduce nuisance lock-ups.
- Braking system activates quickly to arrest fall.
- All components are Z359.12 compliant.

Eligible for service and repair



Class
2
Anchor above or below dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 42 in. (107 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. (2.1 m)
For full clearance requirements, see user instructions	

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 105 in. (267 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	17 ft. 4 in. (5.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Load indicating swivel snap hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized steel
Shock pack	Polyester
Tagline	3mm polyester rope



023-5326

Lodestar LE 50' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- External energy absorber for leading edge use.
- Swivel attachment point offers wide range of motion.
- High strength housing for durability.
- Built-in handle for convenience.
- Optimized walking speeds to reduce nuisance lock-ups.
- Braking system activates quickly to arrest fall.
- All components are Z359.12 compliant.

Eligible for service and repair



Class
2
Anchor above or below dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 11 in. (2.1 m)
For full clearance requirements, see user instructions	

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 108 in. (274 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	17 ft. 6 in. (5.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Load indicating swivel snap hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized steel
Shock pack	Polyester
Tagline	3mm polyester rope

