



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
 322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

### 019-8000 thru 019-8003 2 Person Temporary Kernmantle Rope Horizontal Lifeline



<b>Description</b>	2-Person temporary kernmantle rope horizontal lifeline Tensioner 2 Carabiners 2 O-rings Standard Energy Absorber Transport bag
<b>Part Numbers and Lengths</b>	<b>019-8000:</b> 30' <b>019-8001:</b> 60' <b>019-8002:</b> 80' <b>019-8003:</b> 100'
<b>Attachment Point(s)</b>	2 Carabiners (structural) - 2 O-rings
<b>Materials</b>	16mm Kernmantle rope lifeline Tensile Strength > 11,261 lbs Steel Tensioner Polyester thread Steel Carabiners tensile strength > 5,000 lbs; gate rated at > 3,600 lbs Web Energy Absorber Stamped steel O-rings, rated at 5,000 lbs
<b>Weight Capacity</b>	310 lbs/person 2-person maximum 420 lbs/single user - If using heavyweight harness and lanyard
<b>Applicable Standards</b>	OSHA 1926.502 - OSHA 1910.140