



SPEC SHEET

RPG Cable SRL with Steel Snap Hook End

Design Specifications

| | |
|----------------------|------------------------|
| Cable | 3/16" Galvanized Steel |
| Casing | Heavy-Duty Polymer |
| Anchorage Connector | Swivel Eye |
| Connector | Swivel Steel Snap Hook |
| Gate Strength | 3,600 lbs. |
| Connector Strength | 5,000 lbs. |
| Max. Capacity | 310 lbs. |
| Max. Arrest Distance | 54" CLASS B |
| Avg. Arrest Force | 900 lbs. |
| Breaking Strength | 3,400 lbs. |

Available Lengths

Total Weight

| | |
|-------|---------------------|
| 10 ft | 5.6 lbs - 2.5 kg |
| 20 ft | 7.5 lbs - 3.4 kg |
| 30 ft | 11.6 lbs - 5.2 kg |
| 50 ft | 17 lbs - 7.7 kg |
| 70 ft | 28.8 lbs - 13.06 kg |



Relevant Standards

| | |
|------|--------------|
| OSHA | CFR 1926.502 |
| | CFR 1910.140 |
| ANSI | Z359.14-2021 |
| | A10.32-2012 |

WARNINGS:

- Do not skip user instructions supplied with this product.
- Alteration or misuse of this product or failure to follow instructions may lead to serious injury or even death.



info@frontlinefall.com

www.frontlinefall.com
© 2019

2023 NW 84th Ave, Miami FL, 33122