PRODUCT SPECIFICATIONS

6050228W 5pc Confined Space Davit System with Winch

Modular assembly of functional basic components plus a Personnel Winch joined in a system, allowing you to work with confidence in Confined Space Entry and Retrieval applications and still maintain the flexibility to modify the system to meet your needs. Lightweight aluminum blended with rugged steel elements throughout, the 5pc Davit System operates with full adjustability and enduring performance.

Features:

- 5pc System consists of Davit Arm, 3pc Portable Davit Base and 33" Lower Mast Extension
- Davit Arm adjusts from 12" to 29" and includes Receiver Bracket for FallTech Winch or SRL-R devices
- Portable Davit Base width adjusts from 38" to 65" with 4 preset adjustment positions.
- Davit Base includes integral bullseye level and threaded adjustable leveling feet
- Includes 60' Personnel Winch with Galvanized Steel Cable ***

System Performance Specifications		
Minimum Strength Ratings by Use **		
Moment Rated:	5,750 lbs. Minimum	
Rescue Configuration:	5,000 lbs. Minimum	
Entry/Egress Operation:	1,800 lbs. Minimum	
Number of Users and Weight Capacities		
Rescue Configuration:	2 Users Max. 310 lbs. each	
Entry/Egress Operation:	1 User Max. 310 lbs.	

** see Owner's Manual for complete table of Minimum Load Ratings

Materials		
Davit Arm:	Powder Coated	
Mast Extension:	6061 Aluminum and Zinc Plated Steel	
3pc Portable Base:		

*** for all Material and Performance specifications pertaining to the Personnel Winch included, see Spec Sheet for Part #7297

Relevant Standards	
OSHA:	1926.502



WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

FALLI

• Never connect an Energy Absorbing Lanyard to Hip D-Rings.

