

PRODUCT SPECIFICATIONS

6050328R 5pc Confined Space Davit System with 3-way SRL-R

Modular assembly of functional basic components plus an SRL-R joined in a system, allowing you to work with confidence in Confined Space Entry and Retrieval applications and still maintain the flexibility to modify the system to meet your needs. Lightweight aluminum blended with rugged steel elements throughout, the 5pc Davit System operates with full adjustability and enduring performance.

Features:

- 5pc System consists of Davit Arm, 3pc Portable Davit Base and 33" Lower Mast Extension
- Davit Arm adjusts from 12" to 29" and includes Receiver Bracket for FallTech Winch or SRL-R devices
- Portable Davit Base width adjusts from 38" to 65" with 4 preset adjustment positions.
- Davit Base includes integral bullseye level and threaded adjustable leveling feet
- Includes 60' 3-way SRL-R with Galvanized Steel Cable ***



System Performance Specifications	
Minimum Strength Ratings by Use **	
Moment Rated:	5,750 lbs. Minimum
Rescue Configuration:	5,000 lbs. Minimum
Entry/Egress Operation:	1,800 lbs. Minimum
Number of Users and Weight Capacities	
Rescue Configuration:	2 Users Max. 310 lbs. each
Entry/Egress Operation:	1 User Max. 310 lbs.

** see Owner's Manual for complete table of Minimum Load Ratings

Materials	
Davit Arm:	Powder Coated 6061 Aluminum and Zinc Plated Steel
Mast Extension:	
3pc Portable Base:	

*** for all Material and Performance specifications pertaining to the SRL-R included, see Spec Sheet for Part #7281DG

Relevant Standards	
OSHA:	1926.502

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.