

# PRODUCT SPECIFICATIONS

## 6500128 Davit Arm with Device Receiver Bracket

The Davit Arm is fully adjustable with its preset positions and the integral fine adjustment screw to always keep the anchor point centered over the access location. Offered as a separate component, the Davit Arm can be combined with a variety of mast extension lengths and fixed or portable bases to suit your specific applications.

### Features:

- Davit Arm for use with Mast Extensions, 3pc Portable Base or Vehicle Hitch-mount Base plus Fixed Bases
- Features Telescoping adjustable reach from 12" to 29"
- Includes integral secondary anchor point for Fall Arrest and/or Rescue applications
- Features primary and secondary pulleys for use with multiple devices
- Integral Receiver Bracket accepts FallTech Winch and SRL-R devices



### System Performance Specifications

#### Minimum Strength Ratings by Use \*\*

<b>Moment Rated:</b>	5,750 lbs. Minimum
<b>Rescue Configuration:</b>	5,000 lbs. Minimum
<b>Entry/Egress Operation:</b>	1,800 lbs. Minimum
Number of Users and Weight Capacities	
<b>Rescue Configuration:</b>	2 Users Max. 310 lbs. each
<b>Entry/Egress Operation:</b>	1 User Max. 310 lbs.

\*\* Specifications shown above are for complete 5pc System; see Owner's Manual for complete table of Minimum Load Ratings

### Materials

<b>Davit Arm:</b>	Powder Coated 6061 Aluminum and Zinc Plated Steel
-------------------	---

### Relevant Standards

<b>OSHA:</b>	1926.502 when used with Davit Bases and Mast Extensions
--------------	---

### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.