

PRODUCT SPECIFICATIONS

6500244

Offset Davit Arm with Bracket

The Offset Davit Arm is fully adjustable with its preset positions and the integral fine adjustment screw to position the anchor point centered over the access location. Offered as a separate component, the Davit Arm can be combined with a variety of mast extension lengths and fixed or portable bases to suit your specific applications.

- For use with mast extensions, portable bases and fixed bases.
- Features telescoping adjustable reach from 24" to 44"
- Includes integral secondary anchor point for Fall Arrest and/or Rescue applications.
- Features primary and secondary pulleys for use with multiple devices.
- Integral Receiver Bracket accepts FallTech Winch and SRL-R devices.



Materials

Davit Arm	Powder Coated 6061 Aluminum and Zinc Plated Steel
------------------	---

Relevant Standards

OSHA	OSHA 1926.502 when used with Davit Bases and Mast Extension
-------------	---

System Performance Specifications

Minimum Strength Ratings by Use**

Moment Rated	6,750 ft-lbs. Minimum
Rescue Configuration	5,000 lbs. Minimum
Entry/Egress Operation	1,800 lbs. Minimum

Number of Users and Weight Capacities

Rescue Configuration	2 Users Max. 310 lbs. each
Entry/Egress Operation	1 User Max 310 lbs.

** Specifications shown above are for complete 5pc System; see Owner's Manual for complete table of Minimum Load Ratings

Compatible FallTech Davit Components

6500321	21" Lower Mast Extension
6500433	33" Lower Mast Extension
6500545	45" Lower Mast Extension
6500657	57" Lower Mast Extension
6500844	3pc. Davit Base, 24" to 44"
6501644	Vehicle Hitch Base, 24" to 44"

see Owner's Manual MSC30 for complete list of additional fixed and portable bases