

PRODUCT SPECIFICATIONS

6500321, 6500433, 6500545, 6500657 Lower Mast Extensions

Varied lengths of Lower Mast Extensions allow the user to efficiently adjust the overall height of their Davit System particularly when overhead clearance restrictions are a concern. Mast Extensions are available in the most useful and user-preferred lengths of 21", 33", 45" and 57".

Features:

- Lower Mast Extensions are for use with 3pc Portable Base, Fixed Bases, Vehicle Hitch-mount Base and Davit Arm
- Mast Extensions provide the ability to change the overall anchorage mast height of their system

System Performance Specifications	
Minimum Strength Ratings by Use **	
Moment Rated:	5,750 lbs. Minimum
Rescue Configuration:	5,000 lbs. Minimum
Entry/Egress Operation:	1,800 lbs. Minimum
Number of Users and Weight Capacities	
Rescue Configuration:	2 Users Max. 310 lbs. each
Entry/Egress Operation:	1 User Max. 310 lbs.

** Specifications shown above are for complete 5pc System; see Owner's Manual for complete table of Minimum Load Ratings

Materials	
Mast Extensions:	Powder Coated 6061 Aluminum and Zinc Plated Steel

Relevant Standards	
OSHA:	1926.502 when used with Davit Arm and Davit Bases



WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.