

## 7047QC

### Arc Flash Nomex® 1D Standard Non-belted Full Body Harness, Quick Connect Adjustments

#### Features :

- Features premium overmolded alloy steel dorsal D-ring, quick connect leg and chest buckles, and mating buckle torso adjusters
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, and legs.
- Overmolded quick-connect buckles feature visual indicators showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2014

Material Specifications		Performance Specifications		Compliant With:	
<b>Webbing</b>	Nomex®/Kevlar®; 5,000 lb min. static strength	<b>Static Strength</b>	3,600 lb min.	<b>OSHA</b>	1926.502 and 1910.66
<b>D-ring</b>	Overmolded Alloy Steel; 5,000 lb min. static strength	<b>ANSI User Capacity</b>	130 to 310 l max.	<b>ASTM</b>	F887
<b>Buckles and Adjusters</b>	Overmolded alloy steel; 3,372 lb min. static strength	<b>OSHA User Capacity</b>	130 to 425 lb max.	<b>ANSI</b>	Z359.11-2014

Sizes & Part Numbers						
7047QCS - Small	7047QCM - Medium	7047QCL - Large	7047QCXL - XL	7047QC2X - 2X	7047QC3X - 3X	