PRODUCT SPECIFICATIONS



8078FDQC

Arc Flash Nomex® 2D Climbing Non-Belted Full Body Harness, Overmolded Quick Connect Adjustments

Features:

- Features premium overmolded alloy steel dorsal and sternal D-rings, quick-connect leg and chest buckles, and torso adjusters
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, belt, and legs.
- Shoulder yoke and sub-pelvic leg pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection
- Overmolded quick-connect buckle feature visual indicator showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Includes Arc Flash rated Suspension Trauma Relief Straps
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2021



Material Specifications					
Webbing	Nomex®/Kevlar®; 5,000 lb min. static strength				
D-rings	Overmolded Alloy Steel; 5,000 lb min. static strength				
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength				

Performance Spe	cifications
Static Strength	3,600 lb min.
ANSI User	130 to 310 l
Capacity	max.
OSHA User	130 to 425 lb
Capacity	max.

Com	pliant With:
OSHA	1926.502 and 1910.66
ASTM	F887-20
ANSI	Z359.11-2021
· ·	·

Sizes & Part Numbers						
8078FDQCXS	8078FDQCS	8078FDQCM	8078FDQCL	8078FDQCXL	8078FDQC2X	8078FDQC3X
- XS	- S	- M	- L	- XL	- 2X	- 3X