

8242Y3L

6' Arc Flash Energy Absorbing Lanyard, Double-leg with Choke-loop with Steel Rebar Hooks

Features :

- Features Kevlar® leg webbing throughout
- Includes pliable Soft Pack energy absorber with Nomex® cover.
- Choke-loop dorsal attachment reduces electrical conductivity
- Includes alloy steel rebar hooks for anchorage connections
- Double-leg design facilitates 100% tie-off
- Rebar hooks feature transverse load rated gates
- Complies with ANSI Z359.13-2013 and ASTM F887-13

Material Specifications	
Webbing	Kevlar®; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Choke-loop	Kevlar® webbing; 5,000 lb min. static strength

Performance Specifications	
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ASTM	F887
ANSI	Z359.13-2013