

## 8242YAF

### 6' Arc Flash Energy Absorbing Lanyard, Double-leg with Steel Snap Hooks

#### Features :

- Features Kevlar® leg webbing throughout
- Includes pliable Soft Pack energy absorber with Nomex® cover.
- Includes alloy steel snap hooks for harness attachment and anchorage connections
- Double-leg design facilitates 100% tie-off
- Complies with ANSI Z359.13-2013 and ASTM F887-13

Material Specifications	
<b>Webbing</b>	Kevlar®; 5,000 lb min. static strength
<b>Energy Absorber</b>	Polyester tear-away
<b>Connectors</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	5,000 lb min.
<b>ANSI Lanyard Class</b>	6' free fall
<b>Max. Arrest Distance</b>	48"
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.13-2013
<b>ASTM</b>	F887