

## 82709SB5

9' DuraTech® MAX Personal SRL with Aluminum Rebar Hook, Includes Steel Dorsal Connecting Carabiner

### Features :

- Internal inertial brakes plus the external energy absorber deliver max weight capacity and max below D-ring anchorage distance
- Dyneema® web lifeline resists abrasion while providing trusted strength.
- Overmolded glass-filled nylon housing contributes unmatched impact resistance
- Energy absorber features ViewPack® cover with inspection window and WrapPack label protection
- Integrated aluminum alloy swivel-eye helps to prevent lifeline twisting for smooth operation
- Features aluminum alloy rebar hook anchorage connector; user-supplied dorsal connector required
- Rebar hook features transverse load rated gate
- Includes alloy steel dorsal connecting carabiner
- May be anchored up to 5' below the dorsal D-ring for users weighing up to 425 lb max. with OSHA-only compliance
- Complies with ANSI Z359.14-2014

Material Specifications	
<b>Webbing</b>	Dyneema®/Polyester blend; 4,500 lb min.
<b>Energy Absorber</b>	Polyester tear-away
<b>Anchorage Connector</b>	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Dorsal Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	3,000 lb min.
<b>ANSI SRL Class</b>	Class B
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	54"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.

Compliant With:	
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.14-2014