

PRODUCT SPECIFICATIONS



SoftPack 3' SAL with Self-Tracking Rope Grab

#8353

Features

- For use on 5/8" Poly/PPP rope for fall arrest and restraint.
- ClearPack shock absorber is designed to limit arrest forces to 900 lbs.
- 1" polyester webbing has a tensile strength of 9,800 lbs.
- Double-locking snap hook at the attachment end.

Material Specifications

- Webbing:** *Polyester; Min. 6,000 lbs. tensile strength*
- Energy Absorber:** *Polyester; activation greater than 450 lbs.*
- Connectors:** *Alloy Steel; Min. 5,000 lbs. tensile strength*
- Connector Gates:** *Alloy Steel; Min. 3,600 lbs. front load and side load*

Performance Specifications

- Tensile Strength:** *Min. 5,000 lbs.*
- Max. Capacity:** *310 lbs.*
- Max. Freefall:** *6 feet*
- Max. Arrest Force:** *Less than 900 lbs.*
- Max. Elongation:** *54 inches*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- Never attach a Shock Absorbing Lanyard to the front or side D-rings.



Image shown is #7353

Rope grab meets the requirements of ANSI Z359.1-2007 for strength and dynamic performance

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.