

# PRODUCT SPECIFICATIONS

## Cable Grab

## #7609

### Features

- Rugged alloy-steel construction.
- Detent pin locking system.
- For use on 3/8", 7X19 wire rope climbing systems.
- Meets the requirements of OSHA 1926.502 and ANSI Z359.1-2007 and A10.32-2004.

### Material Specifications

**Body/Cam Lever:** Alloy Steel; Min. 5,000 lbs. tensile strength

### Performance Specifications

**Tensile Strength:** Min. 5,000 lbs.

**Max. Capacity:** 310 lbs.

### Relevant Standards

**OSHA:** CFR1926.502, CFR1910.66

**ANSI:** A359.1-2007 and A10.32-2004

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- **For use on ladder climbing systems installed with an attenuator/energy absorber and under the supervision of a qualified person.**
- **For front D-ring connection only - MAXIMUM ALLOWABLE FREE-FALL IS 2 FEET.**



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.