DURATECH®



Many edges, one block.

Leading edges, sharp edges, soft edges, round edges — DuraTech® Leading Edge SRL from FallTech™ has got you covered.

- Meets ANSI Z359.14-2014. For leading edge applications.
- Anchoring flexibility. Anchor overhead or at foot level. The choice is yours.
- Reduced nuisance lockups. Improved internal design minimizes unintentional lockups so you can move at normal walking speed.
- Low cost of ownership. We know you're hard on your gear so we designed the cast aluminum housing to last.

FEATURES



Extra large, double locking anchorage carabiner included



Rugged lightweight aluminum housing



7/32" galvanized steel cable



External energy absorber with patented ViewPack® cover



Load-indicating swivel snap hook



Stackable housing




7232CLE 1 30' DuraTech® Leading Edge SRL






No matter what edge you're facing, the FallTech™ DuraTech® Leading Edge SRL (self-retracting lifeline) delivers the highest level of fall protection. It's tough enough for daily jobsite abuse, while being light enough to carry and stack. It's been fine-tuned for an exceptionally smooth payout so you can work without worrying about nuisance lockup.



Leading Edge 101

A leading edge is the unprotected side and edge of a floor, roof, or formwork for a floor or other walking/working surface which changes locations as additional levels are constructed. ANSI's standard is any edge with a radius of 0.005". Because the edges are more hazardous, you'll need an SRL that has a stronger cable as well as an external energy absorber to handle the forces of a fall. The DuraTech® LE meets ANSI and OSHA requirements.



You decide where to anchor.

Go ahead and tie off at foot level, up to 5' below your dorsal D-ring. Just be sure you always refer to the instruction manual for calculating minimum required fall clearance. Traditional overhead tie off is always an option too.

Part #	Description	Length	Weight	ANSI SRL Class
7226CLE	> 15' DuraTech® Leading Edge SRL	15'	14 lbs.	А
7227CLE	20' DuraTech® Leading Edge SRL	20'	16.4 lbs.	В
7232CLE	30' DuraTech® Leading Edge SRL	30'	17.5 lbs.	В
7265CLE	60' DuraTech® Leading Edge SRL	60'	26 lbs.	В



Product descriptions and specifications herein may change without notice.

