

# PRODUCT SPECIFICATIONS

## 8039 Roughneck® Premium Bosun Seat

### Features:

- Birch Plywood Seat Board; 23" x 11" x 7/8"
- Molded EVA Seat Pad with PU Cover; 20" x 11" x 2/3"
- Paired Suspension D-Rings
- Heavy Duty Belt with Back Pad
- Includes 2 plated steel Equipment Clips
- Available in sizes Small, Medium, Large and Xtra Large

Material Specifications	
<b>Webbing:</b>	Polyester; 5,000 lbs. Min. Tensile Strength
<b>D-rings:</b>	Alloy Steel; 5,000 lbs. Min. Tensile Strength
<b>Buckles and Adjusters:</b>	Alloy Steel; 3,375 lbs. Min. Tensile Strength

Performance Specifications	
<b>Tensile Strength:</b>	5,000 lbs. Minimum
<b>ANSI User Capacity:</b>	130 to 310 lbs. Max.
<b>OSHA User Capacity:</b>	130 to 425 lbs. Max.

Relevant Standards	
<b>OSHA:</b>	1926.502 and 1910.66

Part #	Size
<b>8039S</b>	Small
<b>8039M</b>	Medium
<b>8039L</b>	Large
<b>8039XL</b>	X-Large



### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.