



**FrenchCreek
Production**

Made in the U.S.A.

Tech-Spec Sheet

Product No. 1769 Girder Anchor

Rev. no.:
Date:
Page:



Product Description:

The 1769 Girder Anchor is a super-quick, super-strong anchorage for structural steel up to 1" thick. To mount the anchor, it is necessary to pre-drill a 3/4" to 1 1/4" hole. The structural steel, and pre-drilled hole must conform to OSHA strength requirements for an anchorage, and must be approved by a competent person.

Use: Installs in one second! The 1769 functions similar to a spring loaded syringe. Pull the spring loaded plunger, push the shaft through an approved hole in steel, then let go of the plunger. The anchor will spring into place, and be ready for use!

Minimum Break: 5000 lbs.

Mounting Instructions:

- Mount onto approved structural steel ONLY
- Structural Steel can be up to 1" thick
- Anchor will mount into pre-drilled hole sizes from 3/4" to 1 1/4"
- Mounting surface MUST have minimum tensile strength of 5000 lbs
- Anchor MUST be properly installed and secured by a competent person

Applicable Standards:

Meets or exceeds OSHA Subpart M and ANSI A10-14 when used in accordance with manufacturers instructions.



**FrenchCreek
Production**

Made in the U.S.A.

Because your life is on the line!

626 Thirteenth Street • Franklin, PA 16323 • Toll Free: 877.228.9327 • 814.437.1808

fax: 814.437.2544 • fcp@velocity.net • www.frenchcreekproduction.com

Proudly Made in the U.S.A.