

# Tech-Spec Sheet

## Model 440A

Rev. no.:

Date:

Page:

### Description

Six foot, dual-leg (100% tie-off) shock-absorbing web lanyard, with #74N (3/4" opening) snaps on ends. Limits fall-arrest forces to 900 pounds when tested to OSHA and ANSI.



### Applicable Standards:

OSHA Subpart M 1926.502, 1910.66  
ANSI A10-14

### Materials:

- #74N snap hook, 3/4" gate opening, cold-formed steel, plated, 100% proof loaded to 3600 pounds, minimum tensile 5000 pounds
- Webbing: Yellow 1" wide nylon, tensile strength 6000 pounds
- Webbing: 1 3/4" nylon tear-away
- Webbing: Black 2" wide nylon, tensile strength 6000 pounds
- Thread: 138 Black bonded nylon
- Thread: 415 White bonded nylon
- Thread: 277 White bonded nylon

Available in lengths 3' to 10'

***Owned, Operated, and Made Exclusively in the U.S.A***

FrenchCreek Production, Inc.  
626 13th Street  
Franklin, PA 16323

[www.frenchcreekproduction.com](http://www.frenchcreekproduction.com)  
e-mail: [fcpc@csonline.net](mailto:fcpc@csonline.net)

Phone: (877) 228-9327  
(814) 437-1808  
Fax: (814) 437-2544