

Tech-Spec Sheet

Model 444AS

Rev. no.:

Date:

Page:

Description

Six foot, dual-leg (100% tie-off) shock-absorbing web lanyard, with #136 (2 1/4" opening) form snaps on ends. Relaxed length of 4 1/2', extended length of 6'. Limits fall-arrest forces to 900 pounds when tested to OSHA and ANSI.

Applicable Standards:

OSHA Subpart M 1926.502, 1910.66

ANSI A10-14



Specifications

- #136 snap hook, 2 1/4" gate opening, cold-formed steel, plated, 100% proof loaded to 3600 pounds, minimum tensile 5000 pounds
- #74N snap hook, 3/4" gate opening, cold-formed steel, plated, 100% proof loaded to 3600 pounds, minimum tensile 5000 pounds
- Webbing: Yellow 1" wide nylon, tensile strength 6000 pounds
- Webbing: 1 3/4" nylon tear-away
- Webbing: Black 2" wide nylon, tensile strength 6000 pounds
- Thread: 138 Black bonded nylon
- Thread: 415 White bonded nylon
- Thread: 277 White bonded nylon

Owned, Operated, and Made Exclusively in the U.S.A

FrenchCreek Production, Inc.
626 13th Street
Franklin, PA 16323

www.frenchcreekproduction.com
e-mail: fcpc@csonline.net

Phone: (877) 228-9327
(814) 437-1808
Fax: (814) 437-2544