

Tech-Spec Sheet

631B Full Body Harness

Rev. no.:

Date:

Page:

Product Description: The 631B Full body harness is light weight, yet extremely durable. Harness features mating (pass-through) buckle leg straps, sub-pelvic strap, hip dee rings for positioning, and adjustable chest strap. Meets or exceeds all mandatory fall protection regulations at time of shipment.

Material Specifications:

- Webbing: Yellow 1 3/4" wide nylon, tensile strength 6000 pounds
- Webbing: Black 1 3/4" wide nylon, tensile strength 6000 pounds
- Dee ring, cold-formed steel, plated, 100% proof loaded to 3600 pounds, minimum tensile 5000 pounds
- Keeper: 2 piece black nylon keeper
- Buckle: Mating buckles, stamped steel, plated, proof loaded to 4500 pounds, minimum tensile, 4000 pounds
- Thread: 138 Black bonded nylon

Sizes Available: Sm-Med, or Med-Xlg

The FrenchCreek difference: Back strap #1 in back below dee ring prevents dee from sliding toward legs, which would leave fallen worker suspended upside-down after head-first fall.

The FrenchCreek difference: Back strap #2 keeps worker from sliding out the back of harness in a fall. OSHA rigid torso tests do not simulate the flexibility of normal human bodies, which can come out of harnesses not "enclosed" in the back.

The FrenchCreek difference: All raw materials are made domestically, and certified.

The FrenchCreek difference: FrenchCreek Production is independently owned, operated, and made in the U.S.A.



FrenchCreek Production, Inc.

626 13th Street

Franklin, PA 16323

www.frenchcreekproduction.com

Phone: (877) 228-9327

(814) 437-1808

Fax: (814) 437-2544