

# Tech-Spec Sheet

## 651 Full Body Harness

Rev. no.:

Date:

Page:



**Product Description:** The 651 Full body harness is light weight, yet extremely durable. Harness features grommet and tongue buckle leg straps, sub-pelvic strap, and adjustable chest strap. Meets or exceeds all mandatory fall protection regulations at time of shipment

### Material Specifications:

- Webbing: Yellow 1 3/4" wide nylon, tensile strength 10000 pounds
- Webbing: Black 1 3/4" wide nylon, tensile strength 6000 pounds
- Dee ring, cold-formed steel, plated, 100% proof loaded to 3600 pounds, minimum tensile 5000 pounds
- Grommets: #2 Rolled rim grommet with spur washer, brass
- Thread: 138 Black bonded nylon
- Thread: 415 Black bonded nylon

**Sizes Available:** Sm-Med, or Med-Xlg



**The FrenchCreek difference:** Back strap #1 in back below dee ring prevents dee from sliding toward legs, which would leave fallen worker suspended upside-down after head-first fall.

**The FrenchCreek difference:** Back strap #2 keeps worker from sliding out the back of harness in a fall. OSHA rigid torso tests do not simulate the flexibility of normal human bodies, which can come out of harnesses not "enclosed" in the back.

**The FrenchCreek difference:** All raw materials are made domestically, and certified.

**The FrenchCreek difference:** FrenchCreek Production is independently owned, operated, and made in the U.S.A.

**Similar Model: 651B** Same as 651, but with hip positioning dee rings.

FrenchCreek Production, Inc.

626 13th Street  
Franklin, PA 16323

[www.frenchcreekproduction.com](http://www.frenchcreekproduction.com)

e-mail: [fcp@csonline.net](mailto:fcp@csonline.net)

Phone: (877) 228-9327

(814) 437-1808

Fax: (814) 437-2544