

# SELF-RETRACTING LIFELINES



**Available in:  
11' & 30'  
Lengths**

Designed to be used as a connecting device in a personal fall arrest system, the Outlaw SRL connects the user's harness to the anchorage point.

The self-retracting lifeline provides freedom of movement to workers performing their job at various heights. As the worker moves toward or away from the device, the spring tensioned cable will retract back into the unit or will draw out of it. The device automatically takes up the slack in the cable keeping it out of the way while minimizing free fall distance if a fall should occur. A centrifugal braking mechanism minimizes free fall distance, and a visual load indicator warns the user that the unit has been involved in a fall.

**Swivel Anchor Loop**  
Swivels 360° to limit line twisting for smooth operation.

**Light, Durable Housing**  
High-Strength, light weight housing provides excellent durability.

## Short Fall Arrest Activation

Unit will stop a fall within inches, reducing fall distances and reducing fall arrest forces to 1,800 lbs or less.

## 310 LB. Weight Capacity

OUTLAW SRL units offer a 310 lb total weight capacity for workers and tools.

## Impact Indicator

Locking snap w/ impact indicator allows for visual inspection of the slightest fall into the unit.



## SRL PART NUMBERS & ORDERING OPTIONS

### OUTLAW SRL MODEL SELECTIONS

Model #	Housing/Swivel Connector	Cable Options	Weight
XR-11G	#354-4 1" opening, steel carabiner	Galvanized Steel Cable	6lbs
XR-11S	#354-4 1" opening, steel carabiner	Stainless Steel Wire	6lbs
XR-11T	#354-4 1" opening, steel carabiner	Technora Rope	6lbs
XR-30G	#354-4 1" opening, steel carabiner	Galvanized Steel Cable	10lbs
XR-30S	#354-4 1" opening, steel carabiner	Stainless Steel Wire	10lbs
XR-30T	#354-4 1" opening, steel carabiner	Technora Rope	10lbs

## Meets Or Exceeds Industry Standards

- OSHA Subpart M 1926.502, 1940.66
- ANSI A10.32-2012, Z359.14-2012
- "CLASS A" SRL - 11' model
- "CLASS B" SRL - 30' model