

G-Link SRL

GUARDIAN
FALL PROTECTION
PERFORMANCE SAFETY GEAR

**Part #: 10947; 10993; 10994; 10995; 10996;
10997; 10998**

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-2012, and ANSI A10.32-2012 regulations.

G-Link SRLs are suitable for the following applications:



Personal Fall Arrest: G-Link SRLs may be used in Personal Fall Arrest applications to support a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. No free fall is permitted. SRL must always be positioned at or above harness dorsal D-ring AND at or below anchor point. Applicable D-ring: Dorsal.



Restraint: G-Link SRLs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully extended length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.

- **Webbing: 7/8" wide, nylon.**
- **Maximum arresting force: 1,800 lbs.; Average arresting force: 900 lbs.**
- **Maximum arresting distance: 54".**
- **Class B SRL.**
- **Available with either aluminum or steel snap hooks or rebar hooks.**
- **Rebar hooks must ONLY be connected to compatible structural rebar.**
- **Always maintain 100% tie-off; always attach disengaged connector to compatible anchor point prior to detaching engaged connector.**

• **NEVER attempt to modify equipment in any way. NEVER attempt to separate SRLs from Connector Bracket.**

Part #	Length	Description
10947	n/a	G-Link Connector Bracket w/High Strength Carabiner
10993	6'	G-Link Dual 6' Retractable System With Aluminum Snap Hooks
10994	10'	G-Link Dual 10' Retractable System With Aluminum Snap Hooks
10995	10'	G-Link Dual 10' Retractable System With Steel Rebar Hooks
10996	6'	G-Link Dual 6' Retractable System With Steel Rebar Hooks
10997	10'	G-Link Dual 10' Retractable System With Aluminum Rebar Hooks
10998	6'	G-Link Dual 6' Retractable System With Aluminum Rebar Hooks