

Parapet Anchor

Part #: 15171

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-07, & ANSI A10.32-12 regulations.

Custom configurations not available. Not repairable.
Contact customer service for details.

Friction Fit Bracket is suitable for the following applications:



Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.



Personal Fall Arrest: Parapet Anchors may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Parapet Anchors may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs.



Use of equipment in unintended applications may result in serious injury or death. NEVER make any connections to guardrail systems.



Fall Prevention: Parapet Anchor Systems may be used in Fall Prevention applications. Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge, and may be used in substitute of Fall Protection or safety netting systems. Installation requirements for Parapet Anchor Systems set forth in this manual MUST be adhered to. Personal Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.



DO NOT use simultaneously as Fall Arrest anchor and Fall Prevention system.

Materials: zinc-plated steel.

Surfaces more than 6' above lower levels require the use of a Fall Prevention or Fall Protection system.

Parapet Anchor adjusts to fit parapet walls between 4" - 20" width.
Minimum parapet wall height: 12".
MAXIMUM spacing between Parapet Anchors: 8'.

All guardrail posts, guardrails, and all other equipment must be selected and deemed compatible by a Competent Person. All guardrails MUST be compatible 2" x 4" or 2" x 6" construction grade lumber, or compatible snap-on metal rails.

UPC-A Code: 672421151717.

