

Miller Scorpion™ PFL

Description

The lightweight, compact design of the 9 ft. (2.7 m) Miller Scorpion Personal Fall Limiter provides workers an affordable alternative to shock-absorbing lanyards. In a head-to-head comparison with shock-absorbing lanyards, the Scorpion web retractable requires less fall clearance, offers greater mobility and prevents tripping hazards.

Materials

Housing:	Thermoplastic Cover/Aluminum Extrusion
Thread:	No.415 6 cord bonded, 3 strand polyester
Snap hook:	Drop Forged Steel
Webbing:	Polyester/Vectran


Technical

Max. Capacity:	310 lbs. (2.7m)
Working Length Capacity:	9 ft. (2.7m)
Max. Arrest Distance	24-in. (.6m)
Avg. Arresting Force:	900 lbs. (4kN) (When tested to ANSI Z359.14)
Max. Peak Arresting Force:	1,800 lbs. (8kN) (When tested to ANSI Z359.14)
Max. Peak Arresting Force:	900 lbs. (4kN) (When tested to OSHA 1926.502 and CSA Z259.2.2)
Ultimate Strength:	3,000 lbs. (13kN)
Lifeline Tension:	1.5 lbs. – 10 lbs (7N – 45N)

Certification

Meets OSHA 1926.502, 1910.66, ANSI A10.32, *ANSI Z359.14-2012 Class A and B, and CSA Z259.2.2 Type 1 requirements.

*ANSI Z359 and CSA Z259-12-11 compliant for connectors that meet the 3,600lb gate requirements.



Miller Scorpion™ PFL



Models	Unit Connector	Lanyard End Connector	Weight
PFL-5	w/D-ring swivel hook	Locking snap hook 3/4" (19mm) gate opening	3.3 lbs. (1.5 kg)
PFL-8	w/captive eye carabiner	Locking snap hook 3/4" (19mm) gate opening	3.5 lbs. (1.6 kg.)
PFL-10	w/D-ring swivel hook	Locking rebar hook 2 1/2" (63mm) gate opening	4.0 lbs. (1.8 kg)
PFL-12	w/carabiner and swivel shackle	Locking rebar swivel hook 2 1/2" (63mm) gate opening	4.4 lbs. (2.0 kg.)
PFL-13	w/D-ring swivel hook	Locking rebar swivel hook 2 1/2" (63mm) gate opening	4.2 lbs. (1.9 kg.)
PFL-14	w/locking snap hook and swivel shackle	Locking rebar swivel hook 2 1/2" (63mm) gate opening	4.6 lbs. (2.1 kg)
PFL-17	w/out unit connector	Web loop for carabiner	2.3 lbs. (1.0 kg)
PFLCMK	Cab Mount bracket w/PFL-15	Locking swivel snap hook 3/4" (19mm) gate opening	9.1 lbs. (4.1 kg)
ANSI Z359.14 and CSA Z259.12-11 Compliant			
PFL-1*	w/out unit connector	Locking snap hook 3/4" (19mm) gate opening	2.9 lbs. (1.3 kg)
PFL-2*	w/steel twist-lock carabiner	Locking snap hook 3/4" (19mm) gate opening	3.5 lbs. (1.6 kg)
PFL-3*	w/stainless steel swivel shackle	Locking snap hook 3/4" (19mm) gate opening	3.1 lbs. (1.4 kg)
PFL-4*	w/carabiner and swivel shackle	Locking snap hook 3/4" (19mm) gate opening	3.7 lbs. (1.7 kg)
PFL-6*	w/rebar hook and swivel shackle	Locking snap hook 3/4" (19mm) gate opening	4.4 lbs. (2.0 kg)
PFL-7*	w/locking snap hook and swivel shackle	Locking snap hook 3/4" (19mm) gate opening	3.7 lbs. (1.7 kg)
PFL-9*	w/carabiner and swivel shackle	Locking rebar hook 2 1/2" (63mm) gate opening	4.4 lbs. (2.0 kg.)
PFL-11*	w/locking snap hook and swivel shackle	Locking rebar hook 2 1/2" (63mm) gate opening	4.4 lbs. (2.0 kg.)
PFL-15*	w/out unit connector	Locking swivel snap hook 3/4" (19mm) gate opening	3.1 lbs. (1.4 kg)
PFL-16*	w/steel twist-lock carabiner	Locking swivel snap hook 3/4" (19mm) gate opening	3.7 lbs. (1.7 kg.)

All units are equipped with a Fall Indicator, in the event of a fall, a flag deploys to indicate the unit has been subjected to fall arresting forces and should be removed from service.



by Honeywell

Toll Free 800.873.5242 (press 4) • hsp techsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.