

Titan[®] Harnesses

SP196 Rev.C

Materials

Webbing (Polyester).....1-3/4" Polyester
Minimum Tensile.....5,000 lbs. webbing
Thread:.....6 cord bonded 3 strand polyester thread. Minimum tensile of 42 lbs.
Grommets.....Brass
Hardware.....Steel
Minimum Tensile strength:
 D-Rings.....5,000 lbs. (22kN)
 Buckles.....4,000 lbs. (18kN)
 * All hardware meets ASTM (50) fifty-hour salt spray test requirements.
Label Materials.....Valeron



Technical

Max Working Load:.....400 lbs -181 kg

Certification:

This product meets the following standards at the time of shipment.

OSHA 1926.502 ANSI A10.32-2004, Z359.1 and CSA Z259.10-M90



Model No.	Web Type	D-Rings	Shoulder Strap Buckles	Leg Strap Buckles	Chest Strap Buckles	Special Features	Weight
T4000	Polyester	Back	Mating	Mating	Mating	Sub-Pelvic Strap & Lanyard Ring	2.55 lbs. (1.16kg)
T4500	Polyester	Back	Mating	Tongue	Mating	Sub-Pelvic Strap & Lanyard Ring	2.99 lbs. (1.36kg)
T4007	Polyester	Back & Side	Mating	Mating	Mating	Sub-Pelvic Strap & Lanyard Ring	3.11 lbs. (1.41kg)
T4507	Polyester	Back & Side	Mating	Tongue	Mating	Sub-Pelvic Strap & Lanyard Ring	3.55 lbs. (1.61kg)
T4577	Polyester	Back & Side	Mating	Tongue	Mating	Sub-Pelvic Strap, Lanyard Ring, Tool Belt, Back Pad & Side D-Rings	4.93 lbs. (2.24kg)

Options shown may vary from actual product and is subject to change without notice.

