

Miller 9 ft. TurboLite™ Personal Fall Limiter

Description

The Miller TurboLite Personal Fall Limiter (PFL) is a compact, lightweight retractable that provides 9 ft. (2.74 m) of working length and arrests a fall quickly in the event of a fall.

Materials

Housing:	High-impact nylon
Hub:	Shock-absorbing engineered co-polymer
Braking Mechanism:	Stainless steel
Webbing:	Vectran core, polyester jacket 1" wide x 0.06" thick (25.4mm x 1.5mm)

Technical

Max. Capacity:	400 lbs. (181.4kg)
Max. Working Length:	9 ft. (2.74m)
Max. Total Arrest Distance:	24 in. (0.6m)
Max. Fall Arrest Force:	900 lbf. (4kN) for 310-lb. (140.6kg) user (when tested to OSHA 1926.502 & CSA Z259.2.2) 1800 lbf. (8kN) for 400-lb. (181.4kg) user
Max./Avg. Fall Arrest Force:	1800 lbf. (8kN) / 900 lbf. (4kN) (when tested to ANSI Z359.14)
Ultimate Strength:	3,000 lbf. (13.34kN)

Fall Clearance

For fall clearance calculations, please see the instruction manual.

Certification

Please see chart on next page.



Miller 9 ft. TurboLite™ Personal Fall Limiter

SKU	Description and Unit Connector	Lanyard End Connector	Weight
OSHA 1926.502, OSHA 1910.66, ANSI A10.32-2012 and ANSI Z359.14-2012 Class A & B and (Hardware meets ANSI Z359.12-2009 and CSA Z259.12-11.)			
MFL-1-Z7/9FT	TurboLite w/Steel Twist-Lock Carabiner w/3,600 lb. Gate Strength	Locking Snap Hook w/3,600 lb. Gate Strength	3.0 lb. (1.4 kg)
MFL-3-Z7/9FT	TurboLite without unit connector	Locking Snap Hook w/3,600 lb. Gate Strength	2.4 lb. (1.1 kg)
MFL-5-Z7/9FT	TurboLite without unit connector	Locking Swivel Snap Hook w/3,600 lb. Gate Strength	2.6 lb. (1.2 kg)
MFL-9-Z7/9FT	TurboLite w/Locking Snap Hook w/3,600 lb. Gate Strength	Locking Snap Hook w/3,600 lb. Gate Strength	3.1 lb. (1.4 kg)
MFL-11-Z7/9FT	TurboLite w/Aluminum Carabiner w/3,600 lb. Gate Strength	Locking Snap Hook w/3,600 lb. Gate Strength	2.5 lb. (1.1 kg)
MFL-12-Z7/9FT	TurboLite w/Aluminum Carabiner w/3,600 lb. Gate Strength	Locking Rebar Hook w/3,600 lb. Gate Strength	3.4 lb. (1.5 kg)
MFL-14-Z7/9FT	TurboLite w/Aluminum Snap Hook w/3,600 lb. Gate Strength	Locking Aluminum Snap Hook w/3,600 lb. Gate Strength	2.8 lb. (1.3 kg)
MFL-15-Z7/9FT	TurboLite w/Aluminum Snap Hook w/3,600 lb. Gate Strength	Locking Rebar Hook w/3,600 lb. Gate Strength	3.6 lb. (1.6 kg)
MFL-16-Z7/9FT	TurboLite without unit connector	Locking Snap Hook w/3,600 lb. Gate Strength	2.3 lb. (1.0 kg)
MFL-17-Z7/9FT	TurboLite without unit connector	Locking Rebar Hook w/3,600 lb. Gate Strength	3.1 lb. (1.4 kg)
OSHA1926.502 & 1910.66			
MFL-1/9FT	TurboLite w/Steel Twist-Lock Carabiner	Locking Snap Hook	2.9 lb. (1.3 kg)
MFL-2/9FT	TurboLite w/Steel Twist-Lock Carabiner	Locking Rebar Hook	3.6 lb. (1.6 kg)
MFL-3/9FT	TurboLite without unit connector	Locking Snap Hook	2.4 lb. (1.1 kg)
MFL-4/9FT	TurboLite without unit connector	Locking Rebar Hook	3.1 lb. (1.4 kg)
MFL-5/9FT	TurboLite without unit connector	Locking Swivel Snap Hook	2.5 lb. (1.1 kg)
MFL-6/9FT	TurboLite without unit connector	Locking Swivel Rebar Hook	3.1 lb. (1.4 kg)
MFL-9/9FT	TurboLite w/Locking Snap Hook	Locking Snap Hook	3.0 lb. (1.4 kg)
MFL-10/9FT	TurboLite w/Locking Snap Hook	Locking Rebar Hook	3.7 lb. (1.7 kg)
MFL-11/9FT	TurboLite w/Aluminum Twist-Lock Carabiner	Aluminum Locking Snap Hook	2.3 lb. (1.0 kg)
MFL-12/9FT	TurboLite w/Aluminum Twist-Lock Carabiner	Aluminum Locking Rebar Hook	3.1 lb. (1.4 kg)

**Miller Twin Turbo™ Fall Protection System
with Twin Turbo G2 Connector
and 9' TurboLite PFLs
(See Specification Sheet SP481)**



MILLER®

by Honeywell



**Miller Twin Turbo™ Fall Protection System
with Twin Turbo D-Ring Connector
and 9' TurboLite PFLs
(See Specification Sheet SP420)**

⚠ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.