



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

*\*\* Item pictured - Part # 018-5024*



### 7' Web SRD Series (Dual Leg)

#### Features and Benefits

Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The 7' Web Series features unique clear plastic housings for enhanced unit inspections and a revolutionary internal braking system, which alleviates the need for an external shock pack in such a small, ergonomic SRL. Fall indicator is sewn into webbing.

#### Length of Web

7 ft (2.13 m)

#### Weight of Unit

*(See Page 2 for configuration options and weights)*

#### Materials

High-strength plastic housing  
.77 in (19.5 mm) Ultrahigh Molecular Weight Webbing  
Forged steel or Aluminum snap hooks  
Forged Steel or Aluminum rebar hooks  
Forged Steel or Aluminum Behind the Web Bracket

#### Hook Ratings

5,000 lbs (2267.96 kg) Tensile Strength  
3,600 lbs (1632 kg) Gate Rated

#### Maximum Arresting Force

<1,800 lbs (816.47 kg)

#### Maximum Arrest Distance

Class A up to 24 in (60.96 cm) if used above Dorsal D-ring  
Class B up to 54 in (137.16 cm) if used up to a maximum of 2 ft below Dorsal D-ring

#### Maximum Working Load

ANSI 130-310 lbs (58.97-140.61 kg)  
OSHA up to 420 lbs (190.51 kg)

#### Webbing Tensile Strength

4,200 lbs (1905.09 kg)

#### Applicable Standards

Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051  
 322 Industrial Court, Concord, NC 28025

## 7' Web SRD Series Dual Leg Configuration Options

DUAL	Web Connection				Housing Connection					Weight In lbs. including carabiner		
	Length in Feet	Material	1.75" Aluminum Snaphook	1.75" Steel Rebar Hook	FS-EX313 Dual Bracket	Steel Carabiner	Aluminum Carabiner	1014 Behind the Web Bracket	1014 Behind the Web Bracket			
018-5016	7	WEB	X			PLASTIC	X	X			5.5	
018-5017	7	WEB		X		PLASTIC	X	X			4.7	
018-5018	7	WEB			X	PLASTIC	X	X			7.5	
018-5019	7	WEB				X	PLASTIC	X	X		6.5	
018-5020	7	WEB	X			PLASTIC	X		X		5.3	
018-5021	7	WEB		X		PLASTIC	X		X		4.5	
018-5022	7	WEB			X	PLASTIC	X		X		7.3	
018-5023	7	WEB				X	PLASTIC	X		X	6.3	
018-5024	7	WEB	X			PLASTIC				X	4.85	
018-5025	7	WEB		X		PLASTIC				X	4.05	
018-5026	7	WEB			X	PLASTIC				X	6.85	
018-5027	7	WEB				X	PLASTIC			X	5.85	
019-5124	7	WEB	X			PLASTIC					X	5.1
019-5125	7	WEB		X		PLASTIC					X	4.3
019-5126	7	WEB			X	PLASTIC					X	7.1
019-5127	7	WEB				X	PLASTIC				X	6.1