

# Commercial Roof Anchors • RLT Risers

## RLT Loop Top Field Weld Risers

**New** ANSI Z359.18 Certification

RLT field welded risers are mfg. to the same specifications as our CRA models and have zero deformation with a 2,500lb load applied to the loop top at any angle. 3rd party certified and tested for compliance. Choose from pre-engineered designs or custom fabrication.

### Specifications:

- 5,000lb Min. Tensile Strength
- Window Washing, PPE, HLL systems
- SST Threaded Vent Hole Plug
- Hot Dip Galvanized, (HDG), 304sst or 316sst
- SAS HLL system engineering
- 3rd party engineering by DH Glabe & Assoc.
- Report available upon request
- Custom anchors available. Contact SAS Sales Team

No.1090 Cast Steel Loop Top

SST Threaded Vent Hole Plug



### Compliance

5,000lb min. tensile strength in any direction the load is applied to the loop top.  
ANSI Z359.18-17 Type A/T  
Window Washing: ANSI/IWCA 1-14.1  
OSHA 1926.502

### Request Unit Pricing

Riser Height	Part Name	Part No.	Material Type	Pass-Thru Top		Riser Material	
				No.	Type	O.D/wt.	Sch
8	RLT-8W	1043-WG	▲HDG	1090	Q235	3.0"	40 0.203
		1043-WS	304sst	1090-S	316sst	4.6lb	
12	RLT-12W	1044-WG	▲HDG	1090	Q235	3.0"	
		1044-WS	304sst	1090-S	316sst	6.9lb	
18	RLT-18W	1045-WG	▲HDG	1090	Q235	3.0"	
		1045-WS	304sst	1090-S	316sst	10.4lb	
24	RLT-24W	1046-WG	HDG	1090	Q235	3.0"	80 0.276
		1046-WS	304sst	1090-S	316sst	17lb	
30	RLT-30W	1047-WG	HDG	1090	Q235	3.0"	
		1047-WS	304sst	1090-S	316sst	22lb	
36	RLT-36W	1048-WG	HDG	1090	Q235	3.0"	
		1048-WS	304sst	1090-S	316sst	26lb	

Max. on site proof load 2,500lb

▲ Stock part

Note 1: Field welded risers cannot be foam filled prior to welding.  
PID label supplied for installation after field welding.