

TWISTER

T2

#1 Trimming System Among Commercial Producers

T2	Type	Feed (lbs/hr)	Feed (kg/hr)
1	Wet	Up to 35	Up to 16
2	Wet	Up to 78	Up to 36
3	Wet	Up to 124	Up to 56
4	Wet	Up to 172	Up to 78
1	Dry	Up to 11	Up to 5
2	Dry	Up to 25	Up to 12



WATCH IT IN ACTION

TWISTERTRIMMER.COM/TWISTER-T2-TRIMMER



T2 Trimmer Features

- Large-Commercial Scale
- Harvest size: ~100+lbs
- Start with Tandem scale up to Triple
- Continuous flow and runtime
- 304 stainless steel tumbler to mitigate risk of contamination
- Nitrided steel blades increase strength and resistance and decrease buildup
- Minimal handling >1 min in tumbler
- Watertight electrical and motors allow for a complete high-pressure washdown
- Wheels allow for easy transport whether indoor or outdoor



TWISTER

T2



SPECIFICATIONS

Product Number	02-10006B
Input Voltage	120V, 60 Hz
Current Draw	15.5A
Blade Motor	1HP
Tumbler Diameter	6in / 10.1cm
Tumbler Slots	50 x .25in/.3cm
Cut Height	.040in / 1mm
Weight	215lbs /97.5kg
Shipping Weight (w/ T2-LC)	420lbs / 190kg
Length	42.5in / 107.9cm
Width	27.5in / 69.9cm
Height	32.5in / 82cm
Circuit Breaker Required	20A / 120V
Connector (plug)	NEMA 5-20P
Certifications	CSA, UL

ACCESSORIES & COMPONENTS

T2 Leaf Collector	23-0117-00-P
T2 Trim Saver	23-0200-01-P
T2 Rail (Single)	24-0400-00-P
T2 Rail Extension	24-0401-01-P
Feed Conveyor (Inbound)	26-0001-02
Quality Conveyor (Outbound)	26-0002-02

ADDITIONAL REQUIREMENTS

Extension Cord

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

CONNECTOR (PLUG)

NEMA 5-20P

Visit twistertrimmer.com or call your Twister Rep for an extensive list of replacement parts or accessories.

