

ACTIVFLEX WRAP

DATA SHEET
02-22-2025

PROTECTIVE SHIELDING FOR CABLES AND EQUIPMENT

- ABRASION RESISTANT
- HIGH TENSILE STRENGTH
- CHEMICAL, OIL & SOLVENT RESISTANT
- GLUE RESISTANT – ADHESIVES WILL NOT BOND
- HIGH TEMPERATURE 570degF
- WELD SPATTER RESISTANT



CABLE WRAP (MARKED & PRE-CUT)



ZIP TIES INSTALL THROUGH PRE-CUT SLITS
ZIP TIE HEAD IS RETAINED – WON'T PULL OUT

PRE-CUT HOLES FOR
EASE OF FASTENING



SIZE	Part #	TYPE	FORMAT	LENGTH
4"	VPG-0461-G3XB	Pre-cut and marked	Sheet	5'
4"	VPG-04625-G3XB	Pre-cut and marked	Roll	25'
12"	VPG-1261-G3XB	Pre-cut and marked	Sheet	5'
12"	VPG-12625-G3XB	Pre-cut and marked	Roll	25'

BULK WRAP (BLANK)



SIZE	Part #	TYPE	FORMAT	LENGTH
4"	VPG-0461B-G3XB	Bulk (blank)	Sheet	5'
4"	VPG-04625B-G3XB	Bulk (blank)	Roll	25'
12"	VPG-1261B-G3XB	Bulk (blank)	Sheet	5'
12"	VPG-12625B-G3XB	Bulk (blank)	Roll	25'
36"	VPG-3661B-G3XB	Bulk (blank)	Sheet	5'
36"	VPG-36625B-G3XB	Bulk (blank)	Sheet	25'

SPECIFICATIONS

	PROPERTY	UNIT	VALUE
GENERAL	COLOR	SIDE 1&2	BLACK
MATERIAL	OUTER	SHEET	PTFE (2-SIDES)
	INNER	WOVEN FIBER	FIBERGLASS
THICKNESS		INCHES	0.18
TEMPERATURE		DEG F (MAXIMUM)	570 deg F
WIDTHS		INCHES	4" to 60"
LENGTHS		FEET	5' to 75'
TENSILE		LBS	250lbs
TEAR STRENGTH		DEGREES	360°
SHELF LIFE		YEARS	35 yrs
FLAMMABILITY		UL	UL 94
UV EXPOSURE			HIGH RESISTANCE
FLEXIBILITY			HIGH FLEX – 2" MIN BEND RADIUS
OTHER		MARKABLE - YES	RESISTANT TO FRAYING

APPLICATION NOTE:

- This product intended for applications within the published operating temperature rating.
- Operators of this and all Weld Dynamix Products are responsible for compliance with measures relating to use, disposal, the protection of persons, equipment, electrical standards and environmental regulations.
- PTFE (Polytetrafluoroethylene) fabrics are subject to various environmental regulations. Users are responsible for ensuring compliance with all applicable federal, state, and local laws regarding its use and disposal.
- **California Proposition 65 Warning:** This product may contain chemicals that are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.

Above information supplied in good faith, based on currently available information. Weld Dynamix, Inc. makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.