

Taps



AZR 5550 / 10 F, AZR 5550 / 15 F AZR 5550 / 20 F AZR 55250 / 10 F

- The installation expenditure of major distribution networks can be reduced substantially.
- Easy installation, just one device instead of five.
- The trunk line DC path is also linked to the tap outlets. This offers remote power to post amplifiers in tap lines.

Model Art. No.	AZR 5550 / 10 F 841113	AZR 5550 / 15 F 841114	AZR 5550 / 20 F 841115	AZR 55250 / 10 F 841151
EAN	4040326411131	4040326411148	4040326411155	4040326411513
Inputs SAT/terrestrial	4 / 1			
Outputs SAT/terrestrial	4 / 1 + 4 / 1			4 / 1 + 4 / 1 + 4 / 1
Frequency range	5 ... 862 MHz 4 x 950 ... 2200 MHz			
Tap loss Tap 1 terrestrial SAT	10 dB 13 ... 10 dB	16 dB 19 ... 15 dB	17 dB 24 ... 20 dB	10 dB 14 ... 10 dB
Tap loss Tap 2 terrestrial SAT	-	-	-	10 dB 14 ... 10 dB
Through loss trunk terrestrial SAT	2,5 ... 2 dB 1 ... 2 dB	1 ... 2 dB 1 ... 2 dB	1 ... 1,5 dB 1 ... 2 dB	4 ... 5 dB 1,5 ... 3 dB
Isolation	Trunk / trunk			
	Trunk / tap			
	Tap / tap			
DC pass	max. 20 V / 1 A			
Ambient temperature	-20 ... +50 °C			
Dimensions (mm)	145 x 130 x 39			