


LEGENDARY SERIES™ HALF INCH (13.2mm) FLOORING

PRODUCT CHARACTERISTICS

Custom engineered dual durometer system built for athletes by athletes. The Legendary 13.2mm product is created through a formulation of high quality post-consumer vulcanized rubber, factory laminated to an EPDM wear layer. Designed to reach the ergonomic needs of high impact training, this slip resistant surface delivers long term durability with low maintenance care. Built to last, powered by Ecore.

COLOR OPTIONS



ASH



SMOKE



GUN METAL



MIDNIGHT

THICKNESS	0.5"
DESCRIPTION	3.2mm EPDM wear layer heat fused to 10mm backing system
CUSTOMIZE	Water jet cut options available for logos, platforms, ladders, etc.
APPLICATION	Weight room, multipurpose fitness, tactical training, rehabilitation, functional workplace environments, etc.
WARRANTY	8 Year Manufacturer's Warranty

PERFORMANCE CRITERIA	TEST METHOD	RESULT
Tensile Strength	ASTM D 412	>200 PSI
Flexibility 1/4" Mandrel	ASTM F 137	Pass
Thermal Conductivity	ASTM C 518	2.1 Btu-in/h-ft-F
Static Load Limit	ASTM F 970 @ 250PS	0.004" Pass
Coefficient of Friction	ASTM D 2047	>0.9
V.O.C. Compliant	ASTM D 5116	Yes
Abrasion Resistance	ASTM D 3389 / EN 649	<1g, 1000 cycle
Resistance to Heat	ASTM F 1514	Δ E <8.0
Pill Test	ASTM D 2859	Pass
Vertical Deflection / Deformation	ASTM F 2772	0.5mm
Surface Effect Slip Resistance	ASTM F 2772	Pass
Ball Rebound	ASTM F 2772	100%
Force Reduction	ASTM F 2772	10%
Sheet Dimension	Manufacturer	4' width by Minimum length of 25 LF