



36 WATT PLUG-IN POWER SUPPLY

| PART NUMBER | DESCRIPTION | DIMENSIONS | AC POWER CORD LENGTH | VOLTS | AMPS |
|--------------|---|--|-----------------------------|-------|------|
| T-36W-12V-PI | 36 watt AC/DC 2 prong plug-in, 12-volt DC 3 AMP | 3-3/4" x 2" x 1-5/16" 95.25 mm x 50.8 mm x 33.34 mm | 56" (4 ft. 8") 1422.4 mm | 12 | 3 |

FEATURES

- No hardwiring required – use an existing hidden outlet
- Easily extend wire between fixture and power supply with Female Barrel Connector (T-FBC)
- Dims on the 12-volt or secondary side with switches, sensors, or the Wireless Dimming System
- 12-volt power supplies over 60 watts are UL Listed for commercial use, and are not UL Class 2 Listed for residential
- 3-year limited warranty
- Designed for indoor application

TECHNICAL INFORMATION

| | |
|------------------------------|-----------------------------|
| Series | Plug-in Power Supply Series |
| Input Voltage | 120 volt AC |
| Output Voltage | 12-volt DC |
| Output Wattage | 36 watts |
| Dimmable | Non-dimmable |
| Rating | cULus Listed |
| Rated Life | 30,000 hrs |
| Mounting | Free placement |
| Operating Temperature | 32°F to 104°F (0°C to 40°C) |
| Environment | Dry location |
| Construction Material | Plastic housing |
| Warranty | 3 years |

INSTALLATION LOCATIONS

- Above Cabinet / Open Soffits
- Interior Wall Cabinet
- Base Cabinets
- Open Covers
- Any Available & Accessible Outlets

DO NOT INSTALL IN AN ATTIC