



# PREMIER COPPER PRODUCTS

PLUMBING PRODUCTS  
DECORATIVE BAR BASKET DRAIN



## D-133PC



### STANDARD INSTALLATION



1. SEPARATE ALL MOUNTING HARDWARE AS SHOWN.
2. APPLY INSTALLATION SILICONE TO THE UNDERSIDE OF STRAINER BODY FLANGE #3.
3. PLACE THE STRAINER BODY #3 INTO SINK HOLE.
4. PLACE RUBBER SEAL #4 ONTO THE TOP OF THE PLASTIC TAILPIECE #5.
5. PLACE TIGHTENING SCREW #2 THROUGH THE CENTER OF THE TOP OF THE STRAINER BODY #3.
6. HOLDING THE PLASTIC TAILPIECE #5 FROM BELOW THE SINK, HAND TIGHTEN THE SCREW #2 THROUGH THE STRAINER BODY #3 AND INTO THE PLASTIC TAILPIECE #5. MAKE SURE THAT YOU TIGHTEN AN ADDITIONAL 1/4 TURN AFTER HAND TIGHTENED.
7. LUBRICATE POST ON BOTTOM OF STRAINER BASKET #1 WITH LIQUID SOAP, THEN PLACE STRAINER BASKET #1 INTO STRAINER BODY #3.
8. ATTACHED FLANGED DRAIN PIPE (NOT SHOWN) THROUGH NUT #7 AND SEAL WASHER #, THEN HAND TIGHTEN NUT #7 TO THE BOTTOM OF PLASTIC TAILPIECE #5

### CARE & CLEANING INSTRUCTIONS

- \* DO NOT USE ALKALINE, ACID BASED DETERGENTS, ABRASIVE POLISHES, SCOURING CLEANSERS, S.O.S. PADS OR SCOTCH BRITE PADS WHEN CLEANING YOUR DECORATIVE LAVATORY DRAINS.
- \* DO NOT LEAVE CORROSIVE CHEMICALS OR SOLIDS LAYING IN THE BOTTOM OF THE SINK BASIN, SUCH AS COFFEE GROUNDS, VINEGAR, ETC.
- \* AFTER NORMAL USE, ALWAYS WIPE THE EXPOSED SURFACE AREA OF YOUR DRAIN WITH A CLEAN SOFT CLOTH. THIS WILL AID IN LIMITING WATER SPOTS.
- \* FOR NORMAL CLEANING, JUST WIPE WITH A DAMP CLOTH AND DRY WITH A SOFT CLOTH.
- \* IF YOU DESIRE TO USE A CHEMICAL CLEANER WHEN CLEANING, WINDEX OR A MILD DISH WASHING SOAP CAN BE USED.