



Dryer for semi-commercial laundry applications

CD10

Features

- Galvanized steel cylinder
- Top, front and side panels standard available in white
- Door opens 180° for easy loading and unloading
- Oversized lint filter located in front for easy cleaning
- Noiseless exhaust blower assures short drying times and low operating costs
- 5 drying programs

Options

- Top, front and side panels in stainless steel
- Coin-operated version for vended laundry applications



OPTIONAL

CD10

Capacity	
Drum volume	201 l
Motor	
Power motor	0,25 kW
Air outlet	
Diameter	102 mm
Heating	
Electric	5,35 kW
Connections	
Gas inlet connection	9,5 mm
Gas consumption	25.000 BTU/hr
Electrical requirements	E- 120/240/60/1-30A - 120/280/60/1-30A - 220/60/1-30A - 230/50/1-30 A - 400/50/3-15A G- 120/60/1-15A - 220/60/1-10A - 230/50/1-10A
Transport data	
Gross weight	OPL: E - 70 kg / G - 73 kg - Vend: E - 73 kg / G - 75 kg
Net weight	OPL: E - 66 kg / G - 68 kg - Vend: E - 68 kg / G - 70 kg
Dimensions H×W×D	OPL: 1027x683x711 mm - Vend: 1126x683x711 mm
Packing dimensions H×W×D	1156x737x832 mm
Packed volume	0,71 m ³

A B C D E F G H I J K

OPL*	1027	1006*	392*	102*	391	683	114*	10	203	711	597
VEND	1126	1006*	392*	102*	391	683	114*	10	203	711	597

* With leveling legs turned into base.

