



# Industrial tumble dryers

## DR120

### Features

- Large door opening for easy loading and unloading
  - extra strong hinge
- Standard galvanized drum
  - oval drum holes preventing damage from standard drywall screws
- Large lint filter
  - easy removal of lint
  - efficient drying
  - self cleaning filter
- Radial airflow
  - drum perforations over the entire surface
  - high production
  - pulley drive system
- Reversing: prevents tangling of the linen
- High performance heating
- OPTimum control (over-dry prevention technology)
  - easy to operate, easy to program
  - 30 programmable cycles
  - 3 cycle types
    - . Time Dry: programmable time and temperature
    - . Auto Dry: 11 programmable automatic dryness levels and programmable temperature
    - . Moisture Dry: will dry to the programmed moisture level at programmed temperature



### Options

- Stainless steel front
- Stainless steel drum
- CARE (Combustion Auto Response Equipped) - A response to laundry combustion
  - prevents early laundry fire by constantly monitoring the temperature in the drum
  - in case of excessive temperature, linen is sprayed with water



## DR120

Capacity 25:1	40,8 kg
Capacity 20:1	51,1 kg
Drum	
Volume	1021 l
Diameter	1118 mm
Depth	1041 mm
Reversible door	no
Door opening diameter	683 mm
Temperature min	38 °C
Temperature max	88 °C
Power motor	
Drum	0,56 kW
Fan	0,75 kW
Exhaust flow rate (50 Hz)	755 l/s
Diameter	254 mm
Power	
Electric heating	60 kW
Gas heating	270.000 BTU/h
Gas heating	68.000 kcal
Steam heating	
@ 6,9 Bar	405.000 BTU/h
	118,5 kW
@ 1,0 Bar	272.000 BTU/h
	79,7 kW
Steam connection inlet	3/4"
Steam connection outlet	3/4"
Gas connection	1"
Noise level	65 dBA
Transport data	
Net weight	578 kg [G/E] - 624 kg [S]
Gross weight	607 kg [G/E] - 656 kg [S]
Packing dimensions HxWxD	2286x1232x1829 mm
Available controls	
OPTimum (OPL only)	standard

A B C D E F G H

DR120 (G/E)	797	826	1242	1268	1725	1153	1178	2177
DR120 (S)	797	826	1242	1268	1725	1153	1178	2174
					depth		width	height

