



TRADE PROFESSIONAL RANGE

For MSDS & Technical Assistance - Email: sales@everesttradepaints.co.uk

TECHNICAL DATA SHEET

HB EPOXY FACTORY FLOOR PAINT - INDUSTRIAL GRADE

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	HB EPOXY FACTORY FLOOR PAINT - INDUSTRIAL GRADE
PRODUCT INFO	A premium two-pack/two-part, highly durable epoxy resin-based floor paint, based on a high build-solvent free epoxy resin, ideal for use in industrial areas such as warehouses, factories and industrial units due to its high build, high durability formula.
COMPONENTS	2 Parts - Two Pack
FINISH	Gloss, Smooth Finish
COLOURS AVAILABLE	Red, Black, White, Dark Grey, Grey, Light Grey, Yellow and Grass Green.
SUITABLE SUBSTRATES	Concrete Floors, Concrete, Cement, Stone and Most porous surfaces
SUPPLIER	Everest Trade Paints
COVERAGE	A 5kg tin will cover approximately 17-20+ square meters per coat.
APPLICATION METHOD	Brush and Roller.
POT LIFE	30 Minutes
WORKING LIFE	45 Minutes
THICKNESS	200 - 250 Microns per coat

AVAILABLE IN 5 KG

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed.



TRADE PROFESSIONAL RANGE

For MSDS & Technical Assistance - Email: sales@everesttradepaints.co.uk

TECHNICAL DATA SHEET

HB EPOXY FACTORY FLOOR PAINT - INDUSTRIAL GRADE

1. Identification of the substance/preparation and of the company/undertaking

RECOAT TIME AT 15°C	12 - 18 Hours at 15°C
CAR TRAFFIC TIME AT 15°C	18 - 36 Hours at 15°C
INDUSTRIAL TRAFFIC TIME AT 15°C	60 Hours at 15°C
FULL CHEMICAL CURE TIME AT 15°C	7 Days
STORAGE	Store away from frost and naked flames.
CLEANER / THINNERS	Clean with White Spirits - No thinning
SHELF LIFE	24 Months if kept sealed and away from frost

AVAILABLE IN 5 KG.

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed.