



APPLICATION GUIDE

Everest Trade Paints - Ultimate Tarmac Restorer and Sealer - High Performance

SURFACE PREPARATION

- Ensure the surface to be sealed is cleaned thoroughly and loose stones are removed before application of the sealer.
- If necessary remove algae or moss prior to application with a fungicidal wash for best results.
- Clean the Tarmac with a power/jet washer on reduced pressure to avoid damaging the surface.
- Make sure the surface is dry before the next steps.

APPLICATION

- Use masking tape on areas adjacent to the neighbour's driveways, lawns and at the bottom of walls to prevent accidental coverage.
- Before application it is advised to thoroughly stir the Tarmac restorer. This will ensure the pigment within the product is mixed correctly and not settled at the bottom of the container. Mixing can be done with a strong stick, broom handle or metal mixing paddle drill attachment.
- We recommend this product is applied with a medium pile double armed roller kit with extension pole, this makes application easier and prevents bending of the roller arm. A paint brush can be used on edges and hard to reach areas.

- Apply the product to a clean, dry Tarmac surface with temperatures above 8 degrees and no chance of rain within 4 hours of last coat being applied.
Make sure surface is 100% dry and free from any moisture or contaminants before application. Do not apply if there is any chance of rain.
- We recommend applying two coats for the best result and performance.
A 20 Litre drum should cover 40 – 60 square meters with 2 coats (This is an estimate and coverage varies depending on surface porosity and condition).
- Under normal conditions, the product will be touch dry in approximately 3 hours.
Do not drive on the coated surface for 24 hours after last coat.
- If applying the advised two coats, allow 3 hours after initial coat before applying the 2nd.
Make sure the coating is touch dry before applying the second coat.

MAINTENANCE

Future maintenance of the surface should be restricted to sweeping and a wash down once or twice per year.

For the average driveway we recommend recoating the driveway roughly every 5 years, this may vary depending on usage and general wear and tear, the Tarmac restorer is a highly durable sealer but will re-quire a re-application from time to time.

STORAGE PRECAUTIONS

Store away from heat and naked flames. Secure lid between uses to prevent paint hardening. Store away from frost.

For further assistance please contact our technical department on 0800 043 8220