



## APPLICATION GUIDE

### Everest Trade Paints – High Performance Polyurethane Block Paving Sealer

---

#### **NOTICE:**

Everest Trade Paints Polyurethane Block Paving Sealer Should Not be used on clay pavers and should only be used on Concrete Block Paving.

#### **NEW BLOCK PAVING**

For best results, clean surface with pressure washer to remove any algae, dirt, grime and general contaminants. Allow the surface to fully dry out (approximately 4 days). Once the driveway has fully dried out the paving should be re-sanded to replace the kiln dried sand removed during the cleaning process.

#### **EXISTING BLOCK PAVING**

Apply after at least 8 weeks after laying the paving to ensure no efflorescence forms.

#### **APPLICATION**

- Make sure the surface is 100% dry and there is no rain forecast for at least 12 hours.  
Don't apply if there is rain forecast within this time
- Make sure sufficient sealer is purchased before application.
- Its advised to wear protective gloves, respirator and goggles while applying the sealer.  
These items are available from our store.
- Don't smoke while applying the sealer.
- Make sure the surface of the block paving and any jointing sand is completely dry and free from dirt.
- Avoid application in hot or cold extremes of temperature (below 12°C or above 27°C).

- Make sure all jointing sand is swept into the joints and does not remain in the chamfers or on top of the block paving.
- Application by double armed roller is advised. A paint brush should be used to cut in on any edges of block paving. Be extra careful to ensure no sand is transferred onto the surface of the blocks.
- We recommend applying two coats for the best result and performance.  
A 20 Litre drum should cover 40 – 50 square meters with 2 coats (This is an estimate and coverage varies depending on surface porosity and condition).
- Under normal conditions, the product will be touch dry in approximately 4 hours.  
Do not drive on the coated surface for 24 hours after last coat.
- If applying the advised two coats, allow 4 hours after initial coat before applying the 2<sup>nd</sup>.  
Make sure the coating is touch dry before applying the second coat.

## MAINTENANCE

Everest Trade Paints Polyurethane Sealers are designed to protect block paving and help minimise maintenance, but as with all block paved surfaces, some degree of routine maintenance is necessary to prevent buildup of lichen, stains or algae growth.

## STORAGE PRECAUTIONS

Store away from heat and naked flames. Secure lid between uses to prevent paint hardening. Store away from frost.

For further assistance please contact our technical department on 0800 043 8220