


ROTEVA

SIZING AND GEOMETRY



Geometry



	S1	S2	S3	S4
A) Seat tube length	400.0 mm	440.0 mm	460.0 mm	480.0 mm
B) Top tube length	565.7 mm	599.4 mm	633.2 mm	665.6 mm
C) Head tube length	110.0 mm	125.0 mm	140.0 mm	150.0 mm
D) Head tube angle	68.0 degrees	68.0 degrees	68.0 degrees	68.0 degrees
E) Seat tube angle	75.0 degrees	75.0 degrees	75.0 degrees	75.0 degrees
F) Chain stay length	465.0 mm	465.0 mm	465.0 mm	465.0 mm
G) Wheelbase	1136.3 mm	1172.0 mm	1207.6 mm	1241.3 mm
H) Stack	618.4 mm	632.3 mm	646.3 mm	655.5 mm
I) Reach	400 mm	430.0 mm	460.0 mm	490.0 mm
J) Bottom bracket drop	60.0 mm	60.0 mm	60.0 mm	60.0 mm
K) Fork length	Geometry designed with a 501 mm axle to crown length rigid fork and 46 mm offset fork			
Recommended rider height	155-170 cm	165-180 cm	175-190 cm	188-195 cm

POTEVA

FRAME DETAILS

Use	Adventure.
Sizes	S1, S2, S3, S4.
Wheel size	27.5 x 4.5", 26 x 4.8" or 29+.
Material	Grade 9 titanium alloy.
Color	Hand brushed titanium.
Front suspension	Rigid or 120 mm.
Rear suspension	Depends on the rear tire pressure.
Water bottle mounts	3 mounts and one Anything Cage mount on the frame. Two Anything Cage mounts on the fork.
Rear and front rack mounts	Yes.
Headset	44 mm ZS top 44 mm External Cup bottom for tapered steerer tube. Headset not included with the frame.
Bottom bracket	100 mm BSA threaded.
Brake mounts	160 mm Post Mount on rear and front. Max rotor size 203 mm.
Rear and front axle	Aluminum through axles included with the frame and fork. 12 mm x 197 mm rear and 15 mm x 150 front spacing. M12 x 1.5 mm thread.
Seat post diameter	31.6 mm.
Seat clamp	34.9 mm titanium clamp included.
Max seat post insertion	S1 300 mm S2 340 mm S3 360 mm S4 380 mm
Cable routing	External for the rear brake and rear derailleur. Internal for the dropper post.
Max tire size	27.5 x 4.5", 26 x 4.8" or 29 x 3.5".
Max chain ring size	34T single ring.
Chain stay outer width	179.9 mm. E.g. Race Face Turbine and Ride XC fatbike cranks are compatible.
Frame weight	2.1 kg for size S3.