

Standard Features

- Mild or stainless steel frame, base and mast
- Diamond tread top plate, mild or stainless steel
- 500 lb, 1,000 lb, 2,000 lb capacity
- Large rubber wheels simplify movement on uneven floors
- (2) Aluminum load cells
- Standard indicator mount with integral handles for the IQ plus 590-DC, 480/480 Plus Legend, and 482/482 Plus Legend

Specifications

End Load Capacity:

100% end loading

mV/V Output:

2 mV/V

Cable length:

9 ft 10 in (3 m)

Height:

Weighing platter: 4.5 in height when in weigh mode

Column Height:

59 in

Warranty:

DeckHand weldment five years, load cells two years, all other components one year

Approvals:

NTEP Certified, CC 98-004, Class III, 2500 d
Measurement Canada approved, AM-5218



APPROVALS



Measurement
Canada
Approved



Part Number/Price

Part #	Overall Size (W x L x H)	Capacity	Est. Weight	Price
Mild Steel				
41293	31 in x 41 in x 4.5 in	500 lb	336 lb	Consult
41294	31 in x 41 in x 4.5 in	1,000 lb	356 lb	Consult
41295	31 in x 41 in x 4.5 in	2,000 lb	373 lb	Consult
Stainless Steel				
41296	31 in x 41 in x 4.5 in	500 lb	336 lb	Consult
41297	31 in x 41 in x 4.5 in	1,000 lb	356 lb	Consult
41298	31 in x 41 in x 4.5 in	2,000 lb	373 lb	Consult

Options/Accessories

Part #	Description	Price
Mild Steel		
43376	500/1,000 lb mild steel ramp	Consult
43378	2,000 lb mild steel ramp	Consult
Stainless Steel		
43377	Ramp assembly, 500/1,000 lb, stainless steel, 25 in x 27 in	Consult
43379	Ramp assembly, 2,000 lb, stainless steel, 25 in x 27 in	Consult
89576	Clam shell for 1260 load cell, stainless steel	Consult
Consult	Smooth top	Consult
DeckHand Portable Scale Optional Indicator Mounts		
41371	Mounting bracket for 320IS with battery option stainless steel	Consult

