

# PRECISE-LOG PL-HW

# Product specifications



## OVERVIEW

The PRECISE-LOG PL-HW is an 8-channel, battery powered, standalone and WIFI-enabled thermistor data logger/Modbus server. The logger measures eight external thermistors and saves data in 8-MB memory.

Embedded WIFI module allows remote data monitoring and downloading. The data logger can be enabled by Modbus TCP protocol and become a Modbus TCP server.

16-bit ADC makes it well suited for science and laboratory applications where precise and accurate measurements are critical.

Its aluminum enclosure makes it excellent in the harshest industrial environment.

Simply power the logger in WIFI covered area and access it from your computer for configuration, downloading, graph viewing and more...

## FEATURES:

### ❖ High Data Resolution:

The 16-bit analog-to-digital converter meets most high-resolution requirements.

### ❖ Large Memory Size:

The 8-Mega-Byte Memory stores years of measurements.

### ❖ Programmable Equations

Configurable equations for temperature, resistance and more...

### ❖ Easy Access:

One Plug & Play USB port makes communications with PC SiteView software super easy. On-board WIFI module provides WIFI Access Point or connects to local network wirelessly, allowing remote monitoring and downloading.

### ❖ 10-Year Battery Life:

The internal lithium battery provides over 10 years of instantaneous logging operation when sampling at an interval of one minute.

### ❖ 2-IN-1 Design:

The logger can operate as portable standalone data logger and be powered by internal battery. Or when powered by external 5VDC power supply, the logger automatically connects to WIFI network and be ready for remote access.

### ❖ Rugged Physical Housing:

The rugged aluminum enclosure makes the PRECISE-LOG data loggers perfect in the harshest industrial environment.

# SiteView Software Overview

SiteView is a PC based application works with all MEI data loggers for downloading, configuration and data analyzing and plotting.

Its user-friendly graphic interface plus powerful functionalities fit both novice and advanced users.

The versatility of custom equation and custom-line equation handle complicated measurement requirements.

SiteView is compatible with Window XP, Vista, 7, 8, 10 operating systems.

## FEATURES:

- ❖ Support USB, Serial port and Ethernet connections for easy local and remote access
- ❖ Fast communication speed up to 115200 bps makes downloading fast
- ❖ Real-time view and chart recording replaces chart recording device
- ❖ Custom equation and custom-line equation solves scientific and laboratory algorithm difficulties
- ❖ Zoom in/zoom out, annotation/label of graph functions provide detailed view of data
- ❖ Multiple file loading allows easy data comparison
- ❖ Dynamic statistics provides detailed information of current zoomed view
- ❖ Scheduled Download automatically backups data regularly to system database
- ❖ Export to CSV, TXT, BMP, JPG, TIF, PNG, GIF file formats.

The screenshot displays the SiteView software interface with several key components highlighted by green arrows:

- Graph View:** A window showing a real-time plot of Voltage DC (mV) over time, with a blue line fluctuating around a red horizontal line.
- Real-Time View:** A window showing a real-time plot of Temperature (°C) over time, with a blue line fluctuating around a red horizontal line.
- Configuration Dialog:** A window showing the configuration settings for the logger, including Description, Sampling Interval, Start Time, and Memory settings.
- Equation Editor:** A window showing the custom equation editor, where users can define mathematical expressions for data processing.
- Tabular View:** A window showing a table of data points, including Date/Time, Channel, and Value.

Date/Time	CH0 (°C)	CH1 (mV)	CH2 (mV)	CH3 (mV)
2019-12-13 19:05:10	22.751	378.119	74.159	74.769
2019-12-13 19:05:15	22.733	378.729	74.769	74.159
2019-12-13 19:05:20	22.726	378.729	74.464	74.464
2019-12-13 19:05:25	22.728	378.729	74.464	74.159
2019-12-13 19:05:30	22.741	377.813	74.159	74.159
2019-12-13 19:05:35	22.758	378.119	74.464	74.159
2019-12-13 19:05:40	22.763	378.729	74.769	74.159
2019-12-13 19:05:45	22.764	377.813	74.769	74.464
2019-12-13 19:05:50	22.747	377.813	74.464	74.464
2019-12-13 19:05:55	22.721	378.119	74.464	74.159
2019-12-13 19:06:00	22.701	378.119	74.464	74.159
2019-12-13 19:06:05	22.684	378.119	74.464	74.464
2019-12-13 19:06:10	22.681	378.119	74.769	74.159
2019-12-13 19:06:15	22.684	377.508	74.464	74.769

## Specification Details

<b>Product Identification</b>	
Product Name	PRECISE-LOG
Model	PL-HW
<b>Inputs</b>	
Connections	Pluggable terminal block for eight external channels
Channels	Eight external thermistor/resistor inputs. (10000 ohms NTC thermistor recommended)
Resolution	0.0018%
Accuracy	+/- 0.2°C (0°C ~ 70°C, 32°F ~ 158°F) ( for 10K NTC thermistor, does not include thermistor probe error)
<b>Alarms</b>	
Channel Alarms	Two editable alarm thresholds per channel.
Alarm Indicator	On-board LED lights in red when in alarm condition.
<b>On-board Memory</b>	
Capacity	8 Mbytes (4 Mega measurements).
Data Retention	Over 20 years.
<b>Sampling &amp; Logging</b>	
Sampling Interval	1 second to 12 hours user selectable
Logging Mode	Stop recording or FIFO when memory is full.
Logging Activation	Programmable instant, start delay or field push-button activation.
<b>Communications</b>	
Interface	USB(USB cable included). WIFI Module (USB wall adapter included): Standard Server Mode: join existing WIFI AP. AccessPoint Server Mode: create AP for PC to join Modbus Protocol for both STA and AP mode
WIFI Module <sup>[1]</sup>	Standard: 802.11b/g/n, Frequency Range: 2.412 – 2.484GHz Transmit Power: 11-18 dBm Receive Sensitivity: -82 to -93 dBm Security: WEP/WPA-PSK/WPA2-PSK Encryption: WEP64/WEP128/TKIP/AES Can be Enabled/Disabled by SiteView software
<b>Battery</b>	
Power	Built-in 3.6V Lithium Battery.
Life Cycle	10 years based on 1 minute sampling interval in stand-alone mode.
<b>Software</b>	
SiteView <sup>[2]</sup>	Configuration, downloading, plotting, scheduled-download, real-time view, custom calibration and custom equation.
Software Requirements	Computer with 1.0 GHz or faster processor 1 GB Memory or higher 10 GB of available hard-drive space or higher Windows XP with SP2 or later, Vista, Window 7, 8, 10 At least one USB port
<b>Physical</b>	
Material	Aluminum enclosure.
Dimension	88 X 64.2 X 24 mm (3.46 X 2.53 X 0.95 inches)
Weight	200g.

Mounting	Probe/Wall-mount holes for hanging/mounting.
<b>Others</b>	
LED Indicator	Tri-Color LED: (can be disabled for power saving) Normal Sampling: green when sampling Alarm: red when sampling Low Battery: amber when sampling.
Operating Environment	-40 ~ +70°C (-40°F ~ 158°F), 0~95%RH non-condensing.
Clock Accuracy	+/- 1 minute per month.
Approvals	CE, FCC
Product Link	<a href="https://www.microedgeinstruments.com/pl-hw.php">https://www.microedgeinstruments.com/pl-hw.php</a>

[1]:

Must be powered by external 5VDC power supply via Mini-USB Port.

[2]: Sold separately.

## LOGGING CAPACITY

Sampling Interval	Enabled Channel	Logging Capacity	Sampling Interval	Enabled Channel	Logging Capacity
1 minute	1	8 years	1 second	1	48 days
1 minute	2	4 years	1 second	2	24 days
1 minute	8	1 year	1 second	8	6 days
10 seconds	1	485 days			
10 seconds	2	242 days			
10 seconds	8	60 days			